



Cooling Tower Frog® Patented

PRODUCT DESCRIPTION

Cortec's Cooling Tower Frog is a Vapor Corrosion Inhibitor (VpCI®) powder packaged in polyvinyl-alcohol (PVA) water-soluble bags. It is specially developed for dry lay-up of cooling towers for seasonal, short, or long-term lay-up. Cooling Tower Frog is effective up to 12 months. This product offers an extremely efficient method of protecting multimetal in enclosed spaces. When the bag is cut open, the VpCIs vaporize and adsorb on all metal surfaces - reaching even recessed areas and interior cavities. The VpCIs form a strong, self-replenishing, protective, molecular layer on the metal. Designed for ease of application, Cooling Tower Frog enables an easy start-up.

FEATURES

- Provides continuous multimetal corrosion protection during lay-up period
- Provides three phase multimetal protection - vapor phase, liquid phase, and the vapor-liquid interface
- Protects inaccessible and recessed surfaces
- Requires little or no surface preparation
- No special preparation necessary prior to start-up
- Eliminates environmental hazards and disposal problems
- Reduces chemical consumption and cost
- Provides easy, convenient, hands-off application
- Enables safe handling
- Easy to apply
- Increased worker productivity
- Replaces hazardous oil-based products
- PVA bags are fully biodegradable

METHOD OF APPLICATION

Remove and discard outer barrier bag.

Dry lay-up:

Place bags flat into the cooling tower basin and slit open water-soluble bags to begin corrosion protection. Two bags treat up to 1,000 gallons or 3,800 liters (133.7 ft³ or 3.8 m³) of enclosed space.

Note: After application, the internal spaces should be sealed from the outside atmosphere.

DIMENSION

Bag 10" x 14" (25 cm x 35 cm)

PHYSICAL PROPERTIES OF POWDER

Appearance	White to off-white powder
pH	6-7 (1% in water)
NVC	98-100

PACKAGING AND STORAGE

Cooling Tower Frog is available in two 4 lb (1.8 kg) bags per box. Store in a sealed container in a dry and cool warehouse. Do not store in conditions above 150°F (66°C).

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer

Revised: 10/9/13. ©Cortec Corporation 1998-2013. All rights reserved. Supersedes: 7/26/11.
© 2013, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.