



EcoLine® Food Machinery Lubricating Grease



FEATURES

- USDA is a Certified biobased product (99% biobased content)
- USDA BioPreferred designated Food Grade Grease for Federal preferred purchasing
- Reduces friction and wear
- Provides superior lubricity to promote longer equipment life
- Biodegradable formula reduces damage to the environment
- Has high flash point for increased safety
- Conforms to USDA H-2 rating
- Conforms to FDA regulation 21CFR
- Meets EPA's EPP criteria
- Manufactured from renewable American-grown crop-based oils
- Meets most manufacturers specifications
- Excellent corrosion protection for ferrous and colored metals
- Biodegradable when released into the environment
- Recommended for both operating and mothballed equipment

PRODUCT DESCRIPTION

EcoLine® Food Machinery Lubricating Grease is a high-quality, corrosion inhibiting lubricant formulated with American-grown natural seed oil. This environmentally friendly lubricating and rust preventative grease, was specifically formulated to meet and exceed the demands of major food and meat processing plants. It conforms to USDA H-2 criteria and USFDA regulations 21CFR. The combination of FDA approved corrosion inhibitors and the specially formulated aluminum based thickener, provides superior protection and lubricity to most conventional greases.

In addition to lubricating, self-healing, and high flash point properties, this biodegradable lubricating grease provides a powerful combination of contact and vapor phase corrosion protection.



TYPICAL PROPERTIES

Property	Data	Method of Evaluation
Appearance	Tan to brown grease	Visual
Non-Volatile		95-98.5
Density		7.4-8 lbs/gal 0.9-0.92 kg/l
Cane Penetration, unworked	310	ASTM-D217
Worked 60 strokes	340	
4-Ball EP, Load Wear Index	N/A	ASTM D-2296
4-Ball Wear Scar, mm	200	ASTM D-2596
Corrosion Test (Salt Spray Cabinet)	200 hours	ASTM B-117
Thicker Type	Aluminum	
Base Oil		
Viscosity		
@40°C, cSt	40	ASTM D-445
@100°C, cSt	8.6	ASTM D-445
Viscosity Index	201	ASTM D2270
Pour Point °C/°F	-12/10.4	ASTM D-97
Flash Point, °C/°F	326/618.8	ASTM D-92
Fire Point, °C/°F	358/676.4	ASTM D-92

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT SAFETY DATA SHEET FOR MORE INFORMATION

METALS PROTECTED

- Carbon Steel
- Stainless Steel
- Cast iron
- Aluminum and alloys
- Copper and alloys

APPLICATION

Product Application:

Product can be applied by brush, roll, or using standard grease guns.

Product Cleanup:

For cleanup of tools and overspray, use alkaline cleaners such as Cortec® VpCI®-414 or mineral spirits.

PACKAGING AND STORAGE

EcoLine® Food Machinery Lubricating Grease is available in 5 gallon (19 liter) plastic containers, 55 gallon (208 liter) metal drums, and 16 oz. (453.6 g) EcoLine® cartridges. EcoLine® Food Machinery Lubricating Grease should be stored sealed. Shelf life is 24 months in sealed containers.

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE.

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 02/05/16. Supercedes: 09/24/13. ©Cortec Corporation 2002-2013 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2013, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed by: