

## **GENERAL PRODUCT SPECIFICATION**

Item No.	MRO100-E				
Date	03-31-08	Replaces	05-31-06	No. Pages	1

## **Product Description:**

Style	Pads; perforated on centerline for dividing in half for smaller applications
Item Size (each)	41 cm x 51 cm
Color	Gray
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %
Structure	96% natural white meltblown nonwoven fibers(<10 microns)
	4% white spunbond nonwoven coverstock(<15-30 microns)
Technology	Meltblown + spunbond
Absorbency	Universal ( <b>Hydrophilic</b> + Oleophilic)
Bonding	Bonded (staggered pattern) + Mechanical entanglement

Thrended Application   Low -Lint Chemical Resistant Solvent for water, On, or solvent base Enquires		Intended Application	Low -Lint Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids
---	--	----------------------	--

Absorbonov Consoity	112 I man hala (gatymatady madiyym yigaagity 12 5y)
Absorbency Capacity	112 l per bale (saturated; medium viscosity-12.5x)

## **Packaging Description:**

Package configuration	1-Case	Pkg. Weight	9.0 kg (7.7 kg)
Items per Package	100-Pads/Case	Pkg. Dimensions	53 cm x 43 cm x
			44cm H
Container type	Carton		

## **Physical Properties**;

Parameter	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	365	37
Caliper	SPCTM-020	mm	5.3	0.5
Absorbency** (med.	SPCTM-004B	gL/gS	12.5	2
Oil)				
Tensile Strength	SPCTM-007	daN	14	1.4
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. \*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.