

## **GENERAL PRODUCT SPECIFICATION**

Item No.	ONO30	٦						
1001111100	01,000	_						
Date	6-29-06	Replaces	3-19-01		No. Pages		1	
Product De	Product Description:							
Style		Oil Net						
Item Size (each)		Bundles						
Color		Multiple						
Composition		Polypropylene filaments or ribbons						
Structure		30 oil nets						
Technology		Meltblown						
Absorbency		Hydrophobic + Oleophilic						
Intended Application		Sorbent mop nets for heavy viscous oil clean up from off of pilings, seawalls, rocks, and the like. Can be reused by rinsing in #1 or #2 fuel oil or similar.						
<b>Absorbency Capacity</b>		182 l per Bale (saturated; medium viscosity- 25x)						
Packaging	Description:							
Package con		Bale		Pkg. Wei	ght		7.4 kg (7.2kg)	
Items per Pa		30 Bundles/Bale			nensions (approx	k.)	33cm x 33cm x 74cm	
Container ty	/pe	Polybag						

## **Physical Properties**;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	<u>Nominal</u>	(+/-)Tolerance
Absorb. Cap.** (med	SPCTM-004	liter/net	1.89	1.13-min
visc.)				
Color	Visual		Multiple	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. \*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.