



**GENERAL PRODUCT SPECIFICATION**

|                 |                   |
|-----------------|-------------------|
| <b>Item No.</b> | <b>SPCMB-0525</b> |
|-----------------|-------------------|

|             |          |                 |     |                  |   |
|-------------|----------|-----------------|-----|------------------|---|
| <b>Date</b> | 11-14-06 | <b>Replaces</b> | New | <b>No. Pages</b> | 1 |
|-------------|----------|-----------------|-----|------------------|---|

**Product Description:**

|                         |   |
|-------------------------|---|
| <b>Style</b>            | Mini Boom   |
| <b>Item Size (each)</b> | 7.5 cm Float, 12.5 cm Skirt, total length 7.5m  |
| <b>Composition</b>      | Vinyl coated Polyester PVC 745 gr/m <sup>2</sup>  |
| <b>Structure</b>        | Floatation material wrapped in cylindrical tubes with a Vinyl coated Polyester PVC fabric skirt hanging into the water held down by a tension member inside the bottom of the skirt to prevent under flow of oil. |
| <b>Connections</b>      | Universal Aluminum or ASTM "Z" Type   |
| <b>Tension Member</b>   | 5mm galvanized chain  |
| <b>Color</b>            | International Yellow  |
| <b>Absorbency</b>       | No absorbency   |

|                             |  |
|-----------------------------|--|
| <b>Intended Application</b> | Containment of oil spills on water in shallow streams and creeks |
|-----------------------------|--|

**Packaging Description:**

|                       |           |                 |                     |
|-----------------------|-----------|-----------------|---------------------|
| Package configuration | Case      | Pkg. Weight     | 8.3 kg              |
| Items per Package     | 1 Section | Pkg. Dimensions | 1.6m x 20cm x 30 cm |
| Container type        |           |                 |                     |

**Physical Properties:**

| <u>Parameter</u>         |        | <u>Units</u> | <u>Nominal</u>       | <u>(+/-)Tolerance</u> |
|--------------------------|--------|--------------|----------------------|-----------------------|
| Actual breaking strength |        | daN          | 818                  |                       |
| Color                    | Visual | -----        | International Yellow | per standard          |

The above properties are "nominal" values used for **PROCESS CONTROL** when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

|                      |  |
|----------------------|--|
| <b>Attributes</b>    | Product will be free of foreign material contamination, rips, holes, and tears.  |
| <b>Labeling</b>      | Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).   |
| <b>Certification</b> | Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery. |