



**GENERAL PRODUCT SPECIFICATION**

|                 |             |
|-----------------|-------------|
| <b>Item No.</b> | UXT330-DP-E |
|-----------------|-------------|

|             |          |                 |          |                  |   |
|-------------|----------|-----------------|----------|------------------|---|
| <b>Date</b> | 03-31-08 | <b>Replaces</b> | 06-12-06 | <b>No. Pages</b> | 1 |
|-------------|----------|-----------------|----------|------------------|---|

**Product Description:**

|                         |  |
|-------------------------|--|
| <b>Style</b>            | Blanket Roll; high strength perforation down the middle for the 38 cm wide dimension, & cross-wise for the 38 cm long dimension.   |
| <b>Item Size (each)</b> | 76 cm wide by 46 m long <b>(240 pads)</b>  |
| <b>Color</b>            | Dark Gray  |
| <b>Composition</b>      | Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %   |
| <b>Structure</b>        | A nonwoven mat where the middle ply is made of randomly oriented Micro-fibers [2-10 micron diameters] and the coverstock layers are lint-resistant & abrasion resistant {controlled porosity} spunbond nonwoven of continuous filaments randomly oriented and thermally point bonded [15-30 micron diameters]. |
| <b>Technology</b>       | Meltblown & Spunbond, 3-ply  |
| <b>Absorbency</b>       | Universal ( <b>Hydrophilic</b> + Oleophilic)   |
| <b>Bonding</b>          | Bonded (staggered pattern) + Mechanical entanglement   |

|                             |  |
|-----------------------------|--|
| <b>Intended Application</b> | Low -Lint Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids |
|-----------------------------|--|

|                            |  |
|----------------------------|--|
| <b>Absorbency Capacity</b> | 158 l per bale (saturated; medium viscosity-13.5x) |
|----------------------------|--|

**Packaging Description:**

|                       |                           |                 |                         |
|-----------------------|---------------------------|-----------------|-------------------------|
| Package configuration | Case                      | Pkg. Weight     | 11.8 kg (10.1kg)        |
| Items per Package     | 1 Roll / Case<br>240 pads | Pkg. Dimensions | 38cm x 38cm x<br>77cm H |
| Container type        | Carton                    |                 |                         |

**Physical Properties:**

| <u>Parameter</u>         | <u>SPC Test Method</u> | <u>Units</u> | <u>Nominal</u> | <u>(+/-)Tolerance</u> |
|--------------------------|------------------------|--------------|----------------|-----------------------|
| Basis Weight             | SPCTM-002A             | G/M2         | 290            | 29                    |
| Caliper                  | SPCTM-020              | mm           | 4.6            | 0.5                   |
| Absorbency ** (med. Oil) | SPCTM-004B             | gL/gS        | 13.5           | 2                     |
| Tensile Strength         | SPCTM-007              | daN          | 14             | 1.4                   |
| Color                    | Visual                 | -----        | Dark Gray      | per standard          |

The above properties are “nominal” values used for **PROCESS CONTROL** when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

\*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

|                      |  |
|----------------------|--|
| <b>Attributes</b>    | Product will be free of foreign material contamination, rips, holes, and tears.  |
| <b>Labeling</b>      | Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).   |
| <b>Certification</b> | Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery. |