



VpCI® ADDITIVES FOR WATER TREATMENT



S-69 N



PRODUCT DESCRIPTION

S-69 N is an additive package for water treatment formulations. It protects ferrous and non-ferrous metals from corrosive contaminants and is an excellent replacement for phosphonate, nitrite, and/or molybdate-based compounds. S-69 N is an organic formulation designed for low level concentrations in field applications. This product contains a unique combination of contact and vapor phase corrosion inhibitors (VpCIs) that will provide corrosion protection, even in partially filled spaces.

TYPICAL APPLICATIONS

S-69 N is an additive to water treatment formulations to replace nitrites, molybdates, phosphonates, amines, and other types of restricted corrosion inhibitors.

DOSAGE

- The concentrations of S-69 N under operating conditions for a closed loop cooling system formulation starts at 2,500-3,000 ppm
- For open loop systems, continuous feed of concentrations of 200-400 ppm can be used to passivate systems for 1-2 weeks, then dosage can be lowered

FEATURES

- Protect ferrous and non-ferrous metals from corrosion and pitting
- Nitrite, chromate, and heavy metal-free
- Contains contact and vapor phase corrosion inhibitors
- Low dosage economy
- Environmentally acceptable formulations
- Readily water-soluble liquids for easy application

TYPICAL PROPERTIES


S-69 N	
Appearance	Clear yellow to amber liquid
pH	9.1-9.6 (Neat)
Solubility in Water	100%
Non-volatile Content	47-52
Density	9.5-9.7 lb/gal (1.14-1.16 kg/l)

PACKAGING AND STORAGE

S-69 N is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums, liquid totes, and bulk. Products should be stored in tightly closed containers. The shelf life is 2 years.



Theoretical Concentration of S-69 based on Nitrogen Reading



FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@corotecvi.com
Internet <http://www.corotecvi.com>

printed on recycled paper  100% post consumer

Revised: 8/26/13. ©Cortec Corporation 2009-2013. Supersedes: 5/15/09
©2013, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.