



**GENERAL PRODUCT SPECIFICATION**

<b>Item No.</b>	<b>UXT60BB</b>
-----------------	----------------

<b>Date</b>	05-04-07	<b>Replaces</b>	11-15-06	<b>No. Pages</b>	1
-------------	----------	-----------------	----------	------------------	---

**Product Description:**

<b>Style</b>	Barrier Backed, Blanket Roll
<b>Item Size (each)</b>	1.52m x 46m
<b>Color</b>	Gray on White
<b>Composition</b>	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %
<b>Structure</b>	Three ply roll. The bottom barrier layer is a white, spunbond nonwoven, treated with a 25 $\mu$ thick film. The middle layer is a gray meltblown nonwoven sorbent comprised of micro-fiber [2-10 micron diameters] mechanically entangled. The top layer is gray spunbond coverstock.
<b>Technology</b>	Meltblown, 3-ply
<b>Absorbency</b>	<b>Hydrophilic</b> + Oleophilic
<b>Bonding</b>	Bonded (staggered pattern) + Mechanical entanglement

<b>Intended Application</b>	Low -Lint Chemical Resistant Barrier Sorbent Blanket Roll for Water, Oil or Solvent Base Liquids
-----------------------------	--

<b>Absorbency Capacity</b>	291 l (saturated; medium viscosity-10x)
----------------------------	---

**Packaging Description:**

Package configuration	Bale	Package Weight (net weight)	26.3 kg (25.2 kg)
Items per Package	1 Roll / Bale	Package Dimensions	43cm x 43cm x 155cm
Container type	Polybag + Twist Tie		

**Physical Properties:**

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Basis Weight	SPCTM-002A	G/M2	360	36
Caliper	SPCTM-003A	mm	4.8	0.48
Absorbency** (med. Oil)	SPCTM-004B	gL/gS	10	2
Tensile Strength	SPCTM-007	daN	18.6	1.8
Color	Visual	-----	Gray/White	per standard

The above properties are “nominal” values used for **PROCESS CONTROL** when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

\*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

<b>Attributes</b>	Product will be free of foreign material contamination, rips, holes, and tears.
<b>Labeling</b>	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
<b>Certification</b>	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.