

VpCI®-411



Before



After

DESCRIPTION

VpCI-411 is a heavy-duty, water-dilutable, D-Limonene-based cleaner/degreaser liquid. This product is designed for extra tough cleaning jobs in industrial and commercial applications. VpCI-411 cleans heavy-duty machinery, shop tools, hoods, parts-in-process, food processing equipment, office equipment, floors, walls, lavatories, and desks. VpCI-411 is very effective in dissolving grease, oil, paraffins, and waxes.

VpCI-411 can be used on all engineering metals and alloys.

Unlike other solvent cleaners available on the market today, which are harmful to human skin and classified as hazardous materials, VpCI-411 is safe to handle. It offers a pleasant odor and is biodegradable. VpCI-411 is also stable in water dilutions from 5% to 50%.

VpCI contains 81% biobased content

VpCI 411 is a USDASM designated industrial cleaner and grease remover for Federal/Federal agency Preferred Purchasing

TYPICAL USES

- Universal cleaning applications
- Machinery or engines coated with grease or oil deposits
- Sheet metal covered with oil or waxy films prior to painting
- Machined parts coated with waxes or greases prior to assembly

- Castings coated with temporary protective oils or wax sealers
- Excellent for removing adhesives
- Removes temporary coatings like Cortec® VpCI-368 or VpCI-389
- Wash hands to remove oils during machining operations
- Petroleum equipment, pipes, vessels, drilling tools, tanks, pipelines, etc.

APPLICATION

Heavy-duty cleaning: 20% to 50% VpCI-411 in water. For heavy-duty cleaning, allow VpCI-411 to penetrate through the dirt and grime and break it free from the metal surface.

Examples of heavily soiled parts:

- Gearboxes
- Engines
- Process and plant machinery
- Oil platforms

Medium-duty cleaning: 10% to 20% VpCI-411 in water

Examples of medium-duty cleaning:

- Production parts
- Steel coils
- General machinery maintenance

Light-duty cleaning: 1% to 5% VpCI-411 in water

Examples of light-duty cleaning:

- Walls and floors
- Lavatories
- Desks and office equipment

PROPERTIES

Appearance	Clear yellow liquid
Density	8.1-8.2 lb/gal (0.97-0.98 kg/l)
pH	7.6-7.8 (Neat)

PACKAGING AND STORAGE

VpCI-411 is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes, and bulk. Shelf life of the product is 12 months.

Minimum storage temperature: 32°F (0°C)

Maximum storage temperature: 120°F (49°C)

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>