



## GENERAL PRODUCT SPECIFICATION

|                 |               |
|-----------------|---------------|
| <b>Item No.</b> | <b>HAZ124</b> |
|-----------------|---------------|

|             |         |                 |         |                  |   |
|-------------|---------|-----------------|---------|------------------|---|
| <b>Date</b> | 6-29-06 | <b>Replaces</b> | 3-20-01 | <b>No. Pages</b> | 1 |
|-------------|---------|-----------------|---------|------------------|---|

### Product Description:

|                         |  |
|-------------------------|--|
| <b>Style</b>            | SOC  |
| <b>Item Size (each)</b> | 7.6 cm d x 366 cm long   |
| <b>Color</b>            | Green with green logo printing   |
| <b>Composition</b>      | Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %   |
| <b>Structure</b>        | Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters)<br>Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber) |
| <b>Technology</b>       | Meltblown + Spunbond + Sealed or Enclosed Ends   |
| <b>Absorbency</b>       | <b>Hydrophilic</b> + Oleophilic  |

|                             |   |
|-----------------------------|---|
| <b>Intended Application</b> | Chemical Resistant "Universal" Sorbent Sock for Spills of Water Base, Oil Base, or Solvent Base Liquids |
|-----------------------------|---|

|                            |   |
|----------------------------|---|
| <b>Absorbency Capacity</b> | 45 l per case (saturated; medium viscosity- 9x) |
|----------------------------|---|

### Packaging Description:

|                       |             |                           |                        |
|-----------------------|-------------|---------------------------|------------------------|
| Package configuration | Case        | Pkg. Weight               | 5.3 kg (4.4kg)         |
| Items per Package     | 4 SOCS/Case | Pkg. Dimensions (approx.) | 56.5cm x 32cm x 37.5cm |
| Container type        | Carton      |                           |                        |

### Physical Properties:

| Parameter               | SPC Test Method | Units | Nominal | (+/-)Tolerance |
|-------------------------|-----------------|-------|---------|----------------|
| SOC Weight              | Gravimetric     | kg    | 1.09    | 0.27           |
| Absorbency** (med. oil) | SPCTM-012B      | gL/gS | 9       | 8-min.         |
| Color                   | Visual          | ----- | Green   | per standard   |

The above properties are "nominal" values used for **PROCESS CONTROL** when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

\*\* The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

|                      |  |
|----------------------|--|
| <b>Attributes</b>    | Product will be free of foreign material contamination, rips, holes, and tears.  |
| <b>Labeling</b>      | Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).   |
| <b>Certification</b> | Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery. |

SPC International, Atealaan 71, I.Z. Klein Gent, B-2200 Herentals, Belgium  
Tel +32(0)14 321855 Fax +32(0)14 320440