

WATER TREATMENT Solutions

Environmentally Safe Vapor phase Corrosion Inhibitors









VpCI® Advantage to Your Formulations

Three level protection—liquid phase, vapor phase, and the interface.

Enhance Your Product Line with Cortec's Environmentally Sound Additives

Cortec's corrosion inhibiting additives enhance your water treatment product line with VpCl® products suitable for wet or dry lay-up of equipment. Cortec's revolutionary VpCl® technology is an environmentally safe alternative to traditional corrosion inhibitor formulations. Cortec® liquids and powders do not contain nitrites, molybdates, hydrazine, or heavy metals. Each of Cortec's product additives has minimal toxicity for maximum environmental protection.

Versatile, Continuous Corrosion Inhibitors

Cortec® VpCls can be formulated into your products to give them temporary, extended, or long term protection capabilities. When your products are enhanced with VpCl® technology they defend against corrosion immediately, even on pre-rusted or scaled surfaces. VpCls are self-replenishing for uninterrupted protection through direct contact, the interface, and vapor phase.

Cost-Effective Solutions

Cortec® additives give your products added market value without drastically increasing their cost. Your customers will be able to eliminate expensive alloys, platings, stainless steel, and other corrosion resistant materials simply by purchasing your VpCl® enhanced products.

Uniquely Formulated Additives for a Broad Range of Industrial Applications

Cortec® researchers and engineers will help you formulate an economical additive suited to the exact chemical specifications of your product line. We use a rigorous assessment, analysis, and testing process to ensure the highest quality and scientific accuracy for your water treatment products applications such as cooling towers, boilers, and condensate lines. Cortec's full range of corrosion inhibiting additives will protect ferrous, non-ferrous and dissimilar metals in water process and piping systems.



Application:

Use Cortec® S-10 as a boiler treatment to keep steam condensate lines safe from pitting, cavitation-erosion, aggressive scaling, and oxygen corrosion.

Add Cortec® S-69 as a building block to your water treatment formulations to protect cooling tower components.

Use Cortec® VpCl®-617 as a finished boiler formulation to prevent mineral scaling, corrosion, and reduce dissolved oxygen content in low to medium pressure boilers.

Use Cortec® VpCl®-645 for protection in sea and salt water.

Cortec® VpCl®-649 provides longterm protection and is effective as a replacement for nitrite and molybdate based formulations for multi metal and niche applications such as injection molding, closed loops and fire sprinkler systems.


Add M-640/640L to automotive, locomotive, industrial ethylene glycol, propylene glycol, water, and glycol/water cooling systems.



With Cortec® water chemistry, you can replace:




- Molybdates
- Phosphonates
- Morpholine
- Hydrazine
- Biomates
- Phosphates



vapor-phase interface

liquid phase



VpCI technology is a revolutionary, environmentally safe, and cost-effective option for corrosion protection. Cortec products protect with a thin, monomolecular protective film. The barrier re-heals and self-replenishes; and can combine with other functional properties for added protective capabilities.

Many Cortec® products:

- Are environmentally friendly
- Offer complete treatment solutions
- Dissolve completely in water
- Formulate easily
- Protect multimetals
- Require only low dosages
- Remain compatible with most biocides
- Are non-hazardous to ship

Product	Description	Applications	Metals Protected	Packaging
Boiler Lizard®	Powder for dry lay-up in premeasured PVA* bags.	Boiler lay-up	Ferrous metals or aluminum	1 water soluble bag per carton, 3.3 lbs. per bag (1.5 kg)
Closed Loop Toad [®]	Powder for wet or dry lay-up in premeasured PVA* bags.	Cooling tower system lay-up	Multi-metal	4 water soluble bags per carton, 2.2 lbs. per bag (1 kg)
Cooling Loop Gator®	Powder for wet or dry lay-up in premeasured PVA* bags.	Cooling tower system lay-up	Multi-metal	4 water soluble bags per carton, 2.2 lbs. per bag (1 kg)
Cooling Tower Frog [®]	Powder for dry lay-up in premeasured PVA* bags.	Cooling tower system lay-up	Multi-metal	2 water soluble bags per carton, 4 lbs. per bag (1.8 kg)
S-69	Organic liquid & powder additives that contain a unique combination of contact and vapor phase inhibitors.	Designed for low level concentration applications	Multi-metal	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
S-69 Powder	Organic powder additive that contains a unique combination of contact and vapor phase inhibitors.	Designed for low level concentration applications	Multi-metal	5 lbs (2.31 kg), 50 lbs (22.7 kg), 100 lbs (45.4 kg)
G-6	Corrosion inhibitor for copper and copper- based alloys, BTA (Benzotriazole).	Designed for direct treatment, circulating cooling systems, functional fluids, and cleaners	Yellow metals	100 lbs (45.4 kg)
G-29	Corrosion inhibitor formulation for the protection of copper, brass, bronze, and ferrous metals.	Primarily designed for metalworking fluid formulations. 50% solution of tolytriazole in alkanolamine	Multi-metal	5 gallon (19 liter), 55 gallon, (208 liter)
M-95	Biodegradable and non-toxic building block for water systems.	Designed for direct treatment, circulating cooling systems, functional fluids, and cleaners	Multi-metal	5 gallon (19 liter), 55 gallon (208 liter), 275 gallon (3.785 liter), and totes
VpCl®-647	Environmentally safe, water-soluble inhibitor for multi-metals. Effective at low dosages.	Open loop cooling water systems	Multi-metal use	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
VpCI®-649 Liquid	Water-soluble inhibitor for multi-metals. Effective at low dosages.	Closed loop cooling, hot water systems, and fire sprinkling systems	Multi-metal protection	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
VpCl®-649 Powder	Water-soluble inhibitor for multi-metals. Effective at low dosages.	Closed loop cooling, hot water systems, and fire sprinkling systems	Multi-metal protection	5 lbs (2.31 kg), 50 lbs (22.7 kg), 100 lbs (45.4 kg)
S-14/S-14F	General purpose water treatment antiscalant. Nonflammable and nontoxic. F version for food grade application.	Effective on scale formation on surfaces in contact with water	Multi-metal use	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
S-14 Bio	Combination of biodegradable scale and corrosion inhibitors.	Open loop systems	Multi-metal use	5 lbs (2.3 kg) pails, 50 lbs (22.7 kg) pails, and 100 lbs (45.4 kg) drums
S-16 Defoamer	Defoamer for aqueous and non-aqueous systems. Specially selected for use in combination with Cortece water-based and oil-based inhibiting systems. Stable under both acidic and basic conditions.	Applications where foaming is a concern	Multi-metal use	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
S-7 Oxygen Scavenger	Oxygen scavenger designed to protect boiler systems against oxygen corrosion (hydrazine-free).	Low-medium pressure boilers	Multi-metal protection	5 lb. (2.3 kg), 50 lb. (23 kg), 100 lb. (45 kg)
S-10/S-10F Corrosion Inhibitor	Corrosion inhibitors for steam condensate lines in boiler systems. S-10F has FDA approved ingredients.	Boiler condensate lines	Multi-metal protection	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
S-15	Total replacement for hydrazine programs in medium to high pressure boilers.	Medium-high pressure boilers	Multi-metal protection	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
VpCl®-615	Phosphonate based corrosion inhibitor for boiler water systems.	Low-medium pressure boilers	Ferrous metals, aluminum alloys and galvanized steel	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk.
VpCl [®] -617	Water-soluble, provides long-term protection against corrosion and scale formation. USDA approved liquid.	Suitable for low to medium pressure boilers	Steel and copper	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk.
	Boiler Lizard® Closed Loop Toad® Cooling Loop Gator® Cooling Tower Frog® S-69 S-69 Powder G-6 G-29 M-95 VpCl®-647 VpCl®-649 Liquid VpCl®-649 S-14/S-14F S-14 Bio S-16 Defoamer S-7 Oxygen Scavenger S-10/S-10F Corrosion Inhibitor S-15 VpCl®-615	Boiler Lizard® Powder for dry lay-up in premeasured PVA' bags. Closed Loop Powder for wet or dry lay-up in premeasured PVA' bags. Cooling Loop Powder for wet or dry lay-up in premeasured PVA' bags. Cooling Tower Powder for dry lay-up in premeasured PVA' bags. S-69 Organic liquid & powder additives that contain a unique combination of contact and vapor phase inhibitors. S-69 Powder Organic powder additive that contains a unique combination of contact and vapor phase inhibitors. G-6 Corrosion inhibitor for copper and copper- based alloys, BTA (Benzotriazole). G-29 Corrosion inhibitor formulation for the protection of copper, brass, bronze, and ferrous metals. M-95 Biodegradable and non-toxic building block for water systems. VpCI®-647 Environmentally safe, water-soluble inhibitor for multi-metals. Effective at low dosages. VpCI®-649 Water-soluble inhibitor for multi-metals. Effective at low dosages. VpCI®-649 Water-soluble inhibitor for multi-metals. Effective at low dosages. S-14/S-14F General purpose water treatment antiscalant. Nonflammable and nontoxic. F version for food grade application. S-16 Defoamer for aqueous and non-aqueous systems. Specially selected for use in combination with Cortece water-based and oil-based inhibiting systems. Stable under both addit and basic conditions. S-7 Oxygen Oxygen scavenger designed to protect boiler systems against oxygen corrosion (hydrazine-free). S-10F has FDA approved ingredients. Total replacement for hydrazine programs in medium to high pressure boilers. VpCI®-615 Phosphonate based corrosion inhibitor for boiler water systems.	Boiler Lizard® Powder for dry lay-up in premeasured PVA* bags. Closed Loop Toad® Cooling tower system lay-up Cooling Loop Powder for wet or dry lay-up in premeasured PVA* bags. Cooling tower system lay-up Cooling Tower Powder for dry lay-up in premeasured PVA* bags. Cooling tower system lay-up Cooling Tower Powder for dry lay-up in premeasured PVA* bags. Cooling tower system lay-up Cooling tower system lay-up	Boiler Lizard® Powder for dry lay-up in premissuand PMV bags. Cooling Loop Powder for wet or dry lay-up in premissuand PMV bags. Cooling Loop Powder for wet or dry lay-up in premissuand PMV bags. Cooling Loop Powder for wet or dry lay-up in premissuand PMV bags. Cooling Tower Powder for wet or dry lay-up in premissuand PMV bags. Cooling Tower Powder for wet or dry lay-up in premissuand PMV bags. Cooling Tower Powder for wet or dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder for dry lay-up in premissuand PMV bags. Cooling Tower Powder lay-up in premissuand PMV bags. Cooling Tower Powder lay-up in premissuand PMV bags. Cooling Tower PMV bags. MAB-metal Cooling Tower Powder dry lay-up in premissuand PMV bags. Cooling Tower PMV bags. MAB-metal Cooling Tower PMV bags. Cooling Tower system lay-up MAB-metal Cooling Tower PMV bags. Cooling Tower system lay-up MAB-metal Cooling Tower PMV bags. Cooling Tower system lay-up MAB-metal Cooling Tower American lay-up MAB-metal Cooling Tower American lay-up Phinarty designed for love level cooling systems. Phinarty designed for love level cooling systems. Phinarty designed for direct heatment, established for mathematics and phinarty designed for mathaloxing systems. Phinarty designed for mathaloxing systems. Phinarty designed for love lay-up the MAB-metal Double tower mathal

PVA*: Polyvinyl Alcohol

	Product	Description	Applications	Metals Protected	Packaging
Engine Coolant	M-640 Powder and M-640 L (Liquid)	Corrosion inhibiting additive for water and ethylene glycol-based, heat exchanger fluids.	Add to antifreeze/coolant fluids	Multi-metal	5 gallon (19 liter), 55 gallon (208 liter) totes, and bulk
	VpCI® Coolant Antifreeze	Ready to use coolant-antifreeze.	Inhibited heat transfer fluid	Multi-metal	5 gallon (19 liter), 55 gallon (208 liter) totes, and bulk
y Fluid Additives	VpCI-609 [®] Powder	Powder that can be pre-dissolved in fresh water.	Fresh water	Ferrous metals, aluminum, and alloys	5 lbs. (2.3kg), 50 lbs. (23kg), and 100 lbs. (45kg) moisture bar- rier bags packed in fiber-lined drums
	VpCl [®] -611	Water-based rust preventive concentrate. Leaves a very thin, transparent, tack free film on the metal surface. Weldable and paintable film is non-toxic, pro-environmental, and contains no nitrite or phosphate inhibitors.	For water blasting or wet abrasive blasting in fresh water.	Alumunim, carbon steel, mild steel, stainless steel, and other ferrous metals	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
rotesting	VpCl®-641	Water-based rust preventative for the protection of ferrous or non-ferrous metals in industrial waters.	Fresh water cooling systems and hydrotesting	Ferrous and non-ferrous metals	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
Hydre	VpCl™-649	Water-based rust preventative for the protection of ferrous or non-ferrous metals in industrial waters.	Fresh water cooling systems and hydrotesting	Ferrous and non-ferrous metals	5 gallon (19 liter) 55 gallon (208 liter), totes and bulk
litives	M-605 series	A non-toxic, environmentally friendly corrosion inhibitor designed specifically as a de-icing salt additive to prevent corrosion due to chlorides.	Additive for deicing salts, and brine systems	Ferrous and non-ferrous metals	5 lb. (2.3 kg), 50 lb. (23 kg), and 100 lb. (45 kg) lined drums
Brine/Salt Water Additives	M-645 Float Coat	Corrosion inhibiting additive to salt waters and brine.	Ballast tanks, hydrotesting, salt water protection	Ferrous and non-ferrous metals	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
Salt Wa	VpCl [®] -644	Corrosion inhibiting additive for water containing inorganic salts, including chlorides.	Cooling/heating systems, hydrotesting applications	Ferrous and non-ferrous metals	5 gallon (19 liter), 55 gallon (208 liter), totes, and bulk
Brine/§	VpCI [®] -645 Marine Use Corrosion Inhibitor	A non-toxic, biodegradable concentrate designed to provide long- term effectiveness in fresh water, salt water, brine, and other highly corrosive solutions containing dissolved sulfide and halogens.	Fresh water, salt water, brine, and other highly corrosive solutions containing dissolved sulfide and halogens	Ferrous and non-ferrous metals	5 gallon (19 liter), 55 gallon (208 liter) ,totes, and bulk
dditives	Bioclean 610	A coconut oil-based product designed for the dispersion and preservation against microbiological growth in water treatment applications.	Microbiological plagued systems	Multi-metal	5 gallon (19 Liter), 55 gallon (208 Liter), liquid totes, and, bulk
Other Additives	BioClean 612	An aliphatic amide based organic penetrating agent and organic deposit dispersant for use in industrial applications.	Microbiological plagued systems	Multi-metal	5 gallon (19 Liter) and 55 gallon (208 Liter)

Visit Us At: www.CortecVCl.com

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corportion believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement product shall be paid by customer.

 ${\tt Cortec}^{\circ} \ {\tt Corporation} \ {\tt shall} \ {\tt have} \ {\tt no} \ {\tt liability} \ {\tt for} \ {\tt any} \ {\tt injury}, \ {\tt loss} \ {\tt or} \ {\tt damage} \ {\tt arising} \ {\tt out} \ {\tt of} \ {\tt the} \ {\tt use} \ {\tt of} \ {\tt or} \ {\tt the} \ {\tt inability} \ {\tt to} \ {\tt use} \ {\tt the} \ {\tt products}.$

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THERE WITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@CortecVCI.com Internet http://www.CortecVCI.com

Internet http://www.CortecVCl.com

Revised: 09/10 Supersedes: 12/09 Pinted on recycled paper 100% post consumer

Cortec®, BioCortec®, BioCortec®, BioCushion®, Boller Lizard®, Closed Loop Toad®, Cooling Tower Frog®, VpCl®, VpCl® Film

Color of Blue®, VpCl=126®, VpCl=60®, VpCl=137®, VmCl=307®, EcolVorte®, EcolAir®, Eco-Corr®, EcolLine®, EcolSeira®, EcoShield®, EcoVeara®, EcoShield®, EcoNeara®, Eco Entitle®, EcoSobil®, Eco-Wara®, Eco-Ninik®, EcoWrap®,

EcoFilm®, Cor-Mitt®, Cort-Pak®, CorShield®, CorSol®, Corrosorbers®, CortVipe®, CorrVerter®, Corr Seal®, CorrLam®, Corr-Fill®, Corrlube®, Cortec®, Electificor®, GalvaCorr®, Siever Corr®, HPRS®, CRI®, MCl®, MCl Grenade®, Milcor®,

Nano VpCl®, and Rust Hunter® are trademarks of Cortec® Corporation.

©Cortec Corporation 2010. All rights reserved.